



Fig.: Order no. 41408

Product description

- Step shelf ladder made of aluminium
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm
- 4-fold edged step-to-side-rail connection
- Smooth-running undercarriage at the lower end
- Space-saving stowage when not in use
- Self-locking spring-loaded castors, Ø 80 mm, at lower end
- Non-slip ladder shoes
- Step spacing: 235 mm
- Ladder width: 420 mm (without castors)
- Ladder width with castors: 600 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

Note: Shelf ladders are manufactured in standard lengths stated here as well as individually made to measure. Please indicate the exact vertical hook-in height - the price is based on the next higher ladder, plus a flat rate for changes of 55.00 euros RRP excluding VAT. Shelf ladders made to size are nonreturnable.





Find our complete range of shelf ladders online at www.steigtechnik.de

Step shelf ladder, mobile



80 mm



Approx. max. working height in m	2.8	3.3	3.8	4.3	4.8	5.3	5.8
Number of steps	6	8	10	12	14	16	18
Vertical hook-in height in m	1.92	2.39	2.86	3.33	3.80	4.27	4.74
Base area in m	0.78	0.95	1.12	1.29	1.46	1.63	1.80
Depth of side-rail in mm	73	73	73	73	73	73	73
Weight in kg	8.4	9.8	11.0	12.3	13.5	14.7	16.0
Order no.	41406	41408	41410	41412	41414	41416	41418

Accessories for shelf ladders

Rail system for shelf ladders



- = 1,000 and 1,500 mm long

ig.: Order no. 30343		1,500 mm -			1,000 mm		
Material	Aluminium	Anodised aluminium	Galvanised steel	Aluminium	Anodised aluminium	Galvanised steel	
Order no	30343	30344	30345	30347	30348	30349	

Brackets



Intermediate holder (1 item required per 1.0 m tube)

Order no. 30310*



Holder with end stop, right-hand

Order no.



Holder with end stop, left hand

30311*	Order no.	30312*

100 101

^{*} Mounting material is not included in the scope of delivery