




Fig.: Order no. 31220 and order no. 19910



Multi-purpose ladder with rungs, 2-section with nivello® stabiliser



Rungs



Appropriate accessories are required for TRBS-compliant work

- Multi-purpose ladder with rungs, made from aluminium
- Stable rectangular tube side-rails
- Grooved square rungs, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Can be used as a stepladder, straight ladder and push-up extension ladder
- Simple height adjustment thanks to insertion hook with lift-off protection
- Corrosion-resistant guide fixtures
- nivello® ladder shoes and nivello® stabiliser (supplied separately)
- Spreader lock with two high-strength polyester straps
- Rung spacing: 280 mm
- Ladder width: 490 mm (without stabiliser)
- Maximum load: 150 kg

Approx. max. working height in m	5.3	6.1	7.2	8.0
Number of rungs	2 x 8	2 x 10	2 x 12	2 x 14
Extended ladder length in m	4.18	5.02	6.14	7.26
Ladder length as double-sided ladder in m	2.35	2.88	3.40	3.98
Base spread in m	1.69	2.15	2.60	2.95
Stabiliser width in m	0.93	0.93	1.20	1.20
Depth of side-rail in mm	73	73	73	73
Weight in kg	12.0	14.5	16.5	20.5
Order no.	31216	31220	31224	31228

Multi-purpose ladder with rungs, 3-section with nivello® stabiliser



Rungs




Appropriate accessories are required for TRBS-compliant work

- Multi-purpose ladder with rungs, made from aluminium
- Stable rectangular tube side-rails
- Grooved square rungs, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Can be used as a stepladder, straight ladder and push-up extension ladder
- Suitable for stairs with ladder length retracted up to 3.0 m
- Simple height adjustment from rung to rung thanks to insertion hook with automatically engaging lift-off protection
- Upper ladder with wall wheels
- nivello® ladder shoes and nivello® stabiliser (supplied separately)
- Spreader lock with two high-strength polyester straps and detachable metal strut
- Rung spacing: 280 mm
- Ladder width: 490 mm (without stabiliser)
- Maximum load: 150 kg



Fig.: Order no. 33308 and order no. 19910



Approx. max. working height in m	5.2	6.9	8.0	9.7	10.8
Number of rungs	3 x 6	3 x 8	3 x 10	3 x 12	3 x 14
Ladder length in m, extended as 3-section straight ladder	4.18	5.86	6.98	8.66	9.78
Ladder length as 2-section straight ladder in m	3.06	4.18	5.02	6.14	6.98
Ladder height as 2 section double-sided ladder with extension part in m	2.97	4.09	4.93	6.05	6.89
Retracted ladder length in m	1.94	2.50	3.00	3.62	4.18
Base spread in m	1.30	1.66	2.08	2.35	2.50
Stabiliser width in m	0.93	0.93	1.20	1.20	1.20
Depth of side-rail in mm	73	73	73	85	98
Weight in kg	14.5	18.0	24.0	31.0	38.0
Order no.	33306	33308	33310	33312	33314

* not for 33312 and 33314

Safety. Made in Germany.



nivello® stabiliser



Spreader lock with two high-strength polyester straps



4-fold edged rung-to-side-rail connection

Details on the relevant product page at www.steigtechnik.de

Suitable accessories

R 13 hook-in step
Order no. 19910'Roll-bar' retrofit kit
Order no. 19634

Find out more from page 118 onwards

Safety. Made in Germany.



nivello® stabiliser



Fittings with sliding guides



4-fold edged rung-to-side-rail connection

Details on the relevant product page at www.steigtechnik.de

Suitable accessories

R 13 hook-in step
Order no. 19910Bridging platform kit
Order no. 30299

Find out more from page 118 onwards