



Fig.: Order no. 20320 with order no. 19910

## Product description



Appropriate accessories are required for TRBS-compliant work

- Rung push-up extension ladder made of aluminium
- Stable rectangular tube side-rails
- Grooved square rungs, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Simple height adjustment from rung to rung thanks to insertion hook with automatically engaging lift-off protection
- Upper ladder, from 14 rungs fitted with wall wheels
- Corrosion-resistant guide fixtures
- Rung spacing: 280 mm
- Ladder width: 500 mm (without stabiliser)
- Available with and without stabiliser
- Maximum load: 150 kg

**Note:** In accordance with standard, the attached push-up extension ladder section cannot be separated from the ladder with lengths over 3.0 m

## Safety. Made in Germany.



nivello®  
ladder shoes



Insertion hook



4-fold edged  
rung-to-side-rail  
connection

Details on the relevant product page at [www.steigtechnik.de](http://www.steigtechnik.de)

## Suitable accessories



Step module  
MaxxStep  
Order no. 19901-19905



R 13 hook-in step  
Order no. 19910

Find out more from page 118 onwards



Secure footing  
outdoors



Ergonomics



Ladder head protection,  
complete set

## Rung push-up extension ladder, 3-section with standard stabiliser



Rungs



Standard stabiliser  
with non-slip ladder shoes (supplied  
loose from ladder length 3.0 m  
upwards)

Approx. max. working height in m	6.9	8.0	9.7	10.8
Number of rungs	3 x 8	3 x 10	3 x 12	3 x 14
Extended ladder length in m	5.86	6.98	8.66	9.78
Retracted ladder length in m	2.50	3.00	3.62	4.18
Stabiliser width in m	0.93	1.20	1.20	1.20
Depth of side-rail in mm	73	73	85	98
Weight in kg	17.2	22.2	29.7	36.7
Order no.	20318	20320	20322	20324



Fig.: Order no. 20322

## Rung push-up extension ladder, 3-section with nivello® stabiliser



Rungs



nivello® stabiliser  
for an extra-secure footing (supplied  
loose from a ladder length of 3.0 m  
upwards)

Approx. max. working height in m	6.9	8.0	9.7	10.8
Number of rungs	3 x 8	3 x 10	3 x 12	3 x 14
Extended ladder length in m	5.86	6.98	8.66	9.78
Retracted ladder length in m	2.50	3.00	3.62	4.18
Stabiliser width in m	0.93	1.20	1.20	1.20
Depth of side-rail in mm	73	73	85	98
Weight in kg	17.2	22.2	29.7	36.7
Order no.	20608	20610	20612	20614



Fig.: Order no. 20612

## Rung push-up extension ladder, 3-section, without stabiliser



Rungs



nivello® ladder shoes  
with patented 2-axis inclination  
technology



Only for intended use  
(e.g. ladder head protection)

Approx. max. working height in m	6.9	8.0	9.7	10.8
Number of rungs	3 x 8	3 x 10	3 x 12	3 x 14
Extended ladder length in m	5.86	6.98	8.66	9.78
Retracted ladder length in m	2.50	3.06	3.62	4.18
Depth of side-rail in mm	73	73	85	98
Weight in kg	16.0	21.0	28.5	35.5
Order no.	20308	20310	20312	20314



Fig.: Order no. 20312

## Accessory packages

In addition to sets that ensure a safe footing, there are also packages with practical aids or to comply with the TRBS regulations.

See page 116 onwards for more