



Fig.: Order no. 21714 with order no. 19910

Product description

Appropriate accessories are required for TRBS-compliant work

- Rung rope-extension ladder made of aluminium
- Stable rectangular tube side-rails
- Grooved square rungs, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Convenient height adjustment from rung to rung thanks to two pulleys with plastic cable
- Upper ladder with wall wheels
- Corrosion-resistant guide fixtures with sliding guides
- Rung spacing: 280 mm
- Ladder width: 470 mm (without stabiliser)
- Available with and without stabiliser
- Maximum load: 150 kg



Suitable accessories





Step module MaxxStep Order no. 19901-19905

R 13 hook-in ster Order no. 19910

Find out more from page 118 onwards

Accessory packages

In addition to sets that ensure a safe footing, there are also packages with practical aids or to comply with the TRBS

See page 116 onwards for more



Secure footing

outdoors









Ladder head protection, complete set

Rung rope-extension ladder, 2-section with standard stabiliser



Number of rungs

Stabiliser width in m

Depth of side-rail in mm

Outer width in mm

Weight in kg

Order no.

Approx. max. working height in m

Extended ladder length in m

Retracted ladder length in m



with non-slip ladder shoes (supplied loose from ladder length 3.0 m

8.3

2 x 14

7.22

4.18

1.20

420

73

22.2

21714



11.4
2 x 20
10.30
5.86
1.20
420

36.7

21720

Rung rope-extension ladder, 2-section with nivello® stabiliser





for an extra-secure footing (supplied loose, from a ladder length



Approx. max. working height in m	8.3	9.4	10.3	11.4
Number of rungs	2 x 14	2 x 16	2 x 18	2 x 20
Extended ladder length in m	7.22	8.34	9.18	10.30
Retracted ladder length in m	4.18	4.74	5.30	5.86
Outer width in mm	420	420	420	420
Stabiliser width in m	1.20	1.20	1.20	1.20
Depth of side-rail in mm	73	85	98	98
Weight in kg	22.2	28.2	33.2	36.7
Order no.	21314	21316	21318	21320

9.4

2 x 16

8.34

4.74

1.20

420

85

28.2

21716

10.3

2 x 18

9.18

5.30

1.20

420

98

33.2

21718

Rung rope-extension ladder, 2-section, without stabiliser





with patented 2-axis inclination



Only for intended use (e.g. ladder head protection)



1.4	
x 20	
0.30	
~~	

Approx. max. working height in m	8.3	9.4	10.3	11.4
Number of rungs	2 x 14	2 x 16	2 x 18	2 x 20
Extended ladder length in m	7.22	8.34	9.18	10.30
Retracted ladder length in m	4.18	4.74	5.30	5.86
Outer width in mm	420	420	420	420
Depth of side-rail in mm	73	85	98	98
Weight in kg	21.0	27.0	32.5	35.5
Order no.	21214	21216	21218	21220

82 83