

## **Product description**



Video of product

- Aluminium work platform
- Sturdy, welded bar design
- 220 mm deep steps made of steel grating ensuring a secure footing
- Top tread area: 550 x 300 mm
- Two lifting castors make it easy to move to new locations (supplied separately)
- Non-slip plastic shoes
- Available with and without handrail
- Maximum load: 150 kg

# Safety. Made in Germany. Welded tube Handrail Non-slip construction plastic shoes Details on the relevant product page at www.steigtechnik.de

#### Suitable accessories





Lifting castors Order no. 50041

Spring-loaded castors with arrester

More information from page 208 onwards

#### Front-end railing for work platform



- 600 mm high, sturdy railing
- For rigid work platforms
- Made of aluminium
- · Completely pre-assembled and easy to
- Only possible in connection with handrails on both sides
- Not for order no. 50031, 50008, 51030, 51031, 51018
- Order no. 50046

### Handrail bracket



- The safety of the work platform is improved with the handrail
- For rigid work platforms
- For an all-round railing two handrails art. no. 50040 and a front-end railing art. no. 50046 are required
- Not for order no. 50031, 50008, 51030, 51031, 51018

| Order no. | 50040 |  |
|-----------|-------|--|
| 0.40.10.  | 00010 |  |

# Work platform rigid steel grating with castors



Steps 220 mm



Step surface R 12 steel grating



| Approx. max. working height | in m 2.4  | 2.6         | 2.8         | 3.0         |
|-----------------------------|-----------|-------------|-------------|-------------|
| Number of steps             | 2         | 3           | 4           | 5           |
| Platform height in m        | 0.40      | 0.60        | 0.80        | 1.00        |
| Base area L x W in m        | 0.73×0.69 | 0.97 x 0.73 | 1.21 x 0.78 | 1.46 x 0.82 |
| Weight in kg                | 11.5      | 16.5        | 21.5        | 26.5        |
| Order no.                   | 51018     | 51019       | 51020       | 51021       |

# Work platform rigid steel grating with castors and handrail



Steps 220 mm



Step surface R12 steel grating



One-sided handrail (supplied separately)







| Approx. max. working height in m | 2.6         | 2.8         | 3.0         |  |
|----------------------------------|-------------|-------------|-------------|--|
| Number of steps                  | 3           | 4           | 5           |  |
| Platform height in m             | 0.60        | 0.80        | 1.00        |  |
| Total height in m                | 1.20        | 1.40        | 1.60        |  |
| Base area L x W in m             | 0.97 x 0.73 | 1.21 x 0.78 | 1.46 x 0.82 |  |
| Weight in kg                     | 17.9        | 22.9        | 27.9        |  |
| Order no.                        | 51023       | 51024       | 51025       |  |

189 188