



Fig.: Order no. 52712

Folding platform ladder with narrow undercarriage



Steps 80 mm

- Platform ladder made of aluminium
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm
- Roomy platform with grooves (650 x 600 mm)
- 4-fold edged step-to-side-rail connection
- With handrail on both sides, 3-sided railing as well as knee and toe boards
- Support section with narrow undercarriage and ballast weight
- Folds together to save space
- Two fixed castors Ø 125 mm with locking devices for quick relocation when folded out
- nivello® ladder shoes
- Generous tool tray
- Outer width: 650 mm (without stabiliser)
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

Approx. max. working height in m	3.15	3.4	3.6	3.85	4.3	4.8	5.25
Number of steps incl. platform	5	6	7	8	10	12	14
Total height in m	2.15	2.38	2.61	2.84	3.30	3.77	4.23
Platform height in m	1.15	1.38	1.61	1.84	2.30	2.77	3.23
Total length folded in m	2.75	3.00	3.25	3.50	4.00	4.50	5.00
Base spread in m	1.40	1.50	1.60	1.70	1.95	2.20	2.40
Stabiliser width in m	0.85	0.85	0.85	0.85	1.00	1.00	1.00
Depth of side-rails ascent section/ support section in mm	73/58	73/58	73/58	73/58	73/58	73/58	73/58
Ballast Weight in kg	30.0	50.0	60.0	80.0	100.0	150.0	160.0
Weight with ballast kg	66.5	86.0	103.0	123.0	146.0	199.5	213.5
Order no.	52705	52706	52707	52708	52710	52712	52714

Safety. Made in Germany.



nivello® ladder shoes



Handrails



Spacious platform

Details on the relevant product page at www.steigtechnik.de

Platform ladder glass-fibre reinforced plastic/aluminium, folding and mobile



80 mm steps



Handrail on both sides



Tested to 1,000 volts

- Platform ladder, GFRP/alu
- Side-rails made of glass-fibre reinforced plastic rectangular tube profiles (min. 10 years ageing resistance)
- Grooved steps with a depth of 80 mm, made of aluminium
- 4-fold edged step-to-side-rail connection
- Platform, GFRP grating (650 x 600 mm)
- With GFRP handrail on both sides, 3-sided railing as well as knee and toe boards
- nivello® ladder shoes
- Support section with narrow stabiliser bar and two fixed castors Ø 125 with locking devices
- Folds together to save space
- Generous tool tray
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg
- Delivery time: approx. 15 days



Fig.: Order no. 36327

Approx. max. working height in m	3.15	3.4	3.6	3.85
Number of steps incl. platform	5	6	7	8
Total height in m	2.17	2.40	2.63	2.87
Platform height up to m	1.17	1.40	1.63	1.87
Base spread in m	1.40	1.50	1.60	1.70
Stabiliser width in m	1.00	1.00	1.35	1.35
Depth of side-rails ascent section/ support section in mm	73/58	73/58	73/58	73/58
Weight in kg	33.0	35.0	38.0	41.0
Order no.	36325	36326	36327	36328

Safety. Made in Germany.



nivello® ladder shoes



Handrails



Spacious platform

Details on the relevant product page at www.steigtechnik.de

Suitable for working near or on live parts

Tested up to 1,000 volts as per DIN EN 61478:2002 Clause 6.5.1 and A1:2004 Category 1 (corresponds to European Standard DIN EN 131-7)

Note: Products with GFRP content are non-returnable due to their sensitivity