



Fig.: Order no. 50104 with order no. 50109

Product description



Video of product benefits

- Aluminium platform stairs single-sided
- Stable rectangular tube side-rails
- Steps with a depth of 200 mm
- Roomy platform (600 x 800 mm)
- 3-sided railing and knee and toe board for safe stance (height: 1,000 mm)
- Four Ø 125 mm self-locking swivel castors, 2 with locking device
- Simple assembly (shipping disassembled)
- In accordance with DIN EN 131-7, handrails are optional on the ascensions of platform ladders with an ascent angle $\geq 60^\circ$
- Available in various step and platform designs
- Maximum load: 150 kg

Note: Bridging platform ladders with spring-mounted castors is not permitted.

Safety. Made in Germany.



Spacious platform



Self-locking swivel castors



Non-slip ladder shoes

Details on the relevant product page at www.steigtechnik.de

Suitable accessories



Handrail

Order no.
50109, 50110, 50114



Safety barrier

Order no. 50124

More information from page 160 onwards

Platform stairs, single-sided with spring-loaded castors



Steps 200 mm



Step surface R9
grooved aluminium



Approx. max. working height in m	2.48	2.7	3.0	3.2	3.5	3.7	3.9
Number of steps incl. platform	2	3	4	5	6	7	8
Platform height without railing in m	0.48	0.72	0.96	1.20	1.44	1.68	1.92
Base area L x W in m	1.07 x 0.72	1.24 x 0.77	1.41 x 0.82	1.58 x 0.88	1.75 x 0.94	1.92 x 1.00	2.09 x 1.06
Depth of side-rails in mm	57	57	57	57	57	57	57
Weight in kg	27.0	30.0	32.0	35.0	38.0	43.0	47.0
Order no.	50102	50103	50104	50105	50106	50107	50108



Steps 200 mm



Step surface R10
steel grating



Approx. max. working height in m	2.48	2.7	3.0	3.2	3.5	3.7	3.9
Number of steps incl. platform	2	3	4	5	6	7	8
Platform height without railing in m	0.48	0.72	0.96	1.20	1.44	1.68	1.92
Base area L x W in m	1.07 x 0.72	1.24 x 0.77	1.41 x 0.82	1.58 x 0.88	1.75 x 0.94	1.92 x 1.00	2.09 x 1.06
Depth of side-rails in mm	57	57	57	57	57	57	57
Weight in kg	32.0	37.0	41.0	46.0	52.0	57.0	63.0
Order no.	51102	51103	51104	51105	51106	51107	51108



Steps 200 mm



Step surface R13
corundum coating R13



Approx. max. working height in m	2.48	2.7	3.0	3.2	3.5	3.7	3.9
Number of steps incl. platform	2	3	4	5	6	7	8
Platform height without railing in m	0.48	0.72	0.96	1.20	1.44	1.68	1.92
Base area L x W in m	1.07 x 0.72	1.24 x 0.77	1.41 x 0.82	1.58 x 0.88	1.75 x 0.94	1.92 x 1.00	2.09 x 1.06
Depth of side-rails in mm	57	57	57	57	57	57	57
Weight in kg	29.5	33.0	35.7	39.3	42.9	48.6	53.4
Order no.	54102	54103	54104	54105	54106	54107	54108