



Fig.: Order no. 50018

### Product description

- Aluminium work platform
- Particularly stable design using rectangular tube side-rails
- Platform depth: 460 mm
- Steps with a depth of 240 mm
- Extendible in 200 mm increments (on request)
- With two sliding handles as standard
- Two Ø 125 mm lifting castors for easy moving from place to place
- Non-slip plastic shoes
- Inclination: 45°
- Available in various step and platform designs
- Maximum load: 200 kg

## Mobile work platform



Steps 240 mm

Step surface R 9  
grooved aluminium

Approx. max. working height in m	2.4	2.6	2.8	3.0
Number of steps	2	3	4	5
Platform height in m	0.39	0.59	0.79	0.99
Base area in m	0.85	1.05	1.25	1.45

Step width 600 mm				
Weight in kg	15.0	19.0	24.5	28.5
Order no.	50011	50012	50013	50014

Step width 800 mm				
Weight in kg	17.5	21.5	27.5	31.5
Order no.	50015	50016	50017	50018

Step width 1,000 mm				
Weight in kg	20.0	25.0	31.5	36.0
Order no.	50019	50020	50021	50022



Fig.: Order no. 50025

### Railing

- Made of round aluminium bar, Ø 40 mm, with knee and toe board
- Side railing optionally right or left as required
- Simple installation

Side railing, one-sided, suitable for	2 steps	3 steps	4 steps	5 steps
Order no.	50023	50024	50025	50026

Front-side railing	600 mm wide	800 mm wide	1,000 mm wide
Order no.	50027	50028	50029

### Lifting castors, reinforced design



- Lifting castors especially suitable for outdoor use and uneven floors
- Ø 150 mm
- 1 set = 2 pcs.

Order no. 50030

### Folding transport handle



- For Ø 40 mm railing bars
- For self-assembly

Order no. 300109



Steps 240 mm

Step surface R 12  
steel grating

Approx. max. working height in m	2.4	2.6	2.8	3.0
Number of steps	2	3	4	5
Platform height in m	0.39	0.59	0.79	0.99
Base area in m	0.85	1.05	1.25	1.45

Step width 600 mm				
Weight in kg	23.0	31.0	38.0	44.0
Order no.	50430	50431	50432	50433

Step width 800 mm				
Weight in kg	28.0	38.0	46.0	55.0
Order no.	50434	50435	50436	50437

Step width 1,000 mm				
Weight in kg	33.0	45.0	55.0	63.0
Order no.	50438	50439	50440	50441