



Work platform



Platform surface R 10 aluminium chequered plate

- Aluminium work platform
- Sturdy, welded bar design
- Top tread area: 1,000 x 600 mm
- Platform surface made of non-slip aluminium chequered plate
- Low weight for easy transport
- Non-slip plastic shoes
- Maximum load: 150 kg

| Approx. max. working height in m | 2.25 |
|-------------------------------------|--------------------|
| Number of steps | 1 |
| Platform height in m | 0.25 |
| Transport dimensions L x W x H in m | 1.04 x 0.69 x 0.25 |
| Weight in kg | 8.0 |
| Order no. | 50032 |



Modular work platform



250 mm steps





- Welded and straight aluminium design.
- 250 mm deep steps and large tread area made of aluminium chequered plate for secure stance
- Non-slip plastic shoes
- Optional extension of the basic module by additional modules for a larger standing area or more steps
- Optional fixed castors for easy relocation or floor mounting bracket for stationary use
- Can also be used as a walkway with access from both sides with a bridging step module
- Maximum load: 150 kg



Fig.: Order no. 50410 and order no. 50411









| | Basic module | Extension module 1 | Extension module 2 | Bridging step module |
|----------------------------------|--------------|--------------------|--------------------|----------------------|
| Approx. max. working height in m | 2.4 | 2.4 | 2.6 | - |
| Number of steps | 2 | 2nd step | 3rd step | - |
| Platform height in m | 0.40 | 0.40 | 0.60 | - |
| Base area L x W in m | 0.59 x 0.65 | 0.33 x 0.65 | 0.33×0.65 | 0.56 x 1.00 |
| Weight in kg | 7.0 | 4.5 | 6.0 | 7.5 |
| Order no. | 50410 | 50411 | 50412 | 50415 |

Suitable accessories



Fixed castors Order no. 50418



Floor mounting bracket Order no. 50419

More information from page 208 onwards

200 201