



Fig.: Order no. 600449

45° stairs with platform



Inclination angle 45°



Step surface R 9 grooved aluminium

- Fixed stairs with aluminium platform and inclination 45°
- Step and platform widths: 600, 800 or 1.000 mm
- Platform length: 460 mm
- Last step (depth: 225 mm) mounted at the same height as the platform (total tread area: 685 mm)
- Standard step and platform design in grooved aluminium (R 9), optionally also available with other surfaces (see overview on right)
- Handrail and railing on one side, Ø 40 mm, with bolted connecting elements as standard (height: 1,100 mm)
- front side railing available at an additional charge
- Second handrail optional (necessary in case of wall clearance > 120 mm in accordance with DIN EN ISO 14122-3)
- Lower side-rail ends with robust foot brackets for floor-mounted installation
- Easy installation thanks to delivery in pre-assembled modules including assembly instructions
- For stairs with a step width of 800 or 1,000 mm and a vertical height of 3,300 mm or more, a central support is required (at a surcharge or provided on site)
- If no support surfaces or attachments are provided by the customer, a triangular console must be used for fastening
- Maximum load: 1.5 kN / m², step load 150 kg, total load 300 kg




Your individual product in just a few clicks!

You can configure:

- Length, Width, Height
- Handrail and railing design (e.g. push-fit)
- Stainless steel connecting parts
- Fastening options

www.steigtechnik.de/konfigurator



Number of steps	4	5	6	7	8	9
A Total height in mm	1,930	2,150	2,350	2,560	2,770	2,970
B Vertical height in mm	830	1,050	1,250	1,460	1,670	1,870
C Base area in mm	1,518	1,751	1,959	2,171	2,384	2,596

Step width 600 mm	Order no.	600424	600425	600426	600427	600428	600429
-------------------	-----------	--------	--------	--------	--------	--------	--------

Step width 800 mm	Order no.	600444	600445	600446	600447	600448	600449
-------------------	-----------	--------	--------	--------	--------	--------	--------

Step width 1,000 mm	Order no.	600464	600465	600466	600467	600468	600469
---------------------	-----------	--------	--------	--------	--------	--------	--------

Second handrail* at a surcharge	Order no.	600504	600505	600506	600507	600508	600509
---------------------------------	-----------	--------	--------	--------	--------	--------	--------

*incl. Railing

Optional step surfaces configurable and on request

	Step depth in mm	Step width in mm
Step surface R 12 steel grating	225	600
		800
		1,000
Step surface R 13 anodised aluminium grating	225	600
		800
		1,000
Step surface R 13 perforated steel cover	225	600
		800
		1,000
Step surface R 13 perforated aluminium cover	225	600
		800
		1,000
Step surface R 13 corundum surface R 13 black or yellow	225	600
		800
		1,000

Step depth can differ according to the standard and design

Accessories



Triangular console

Order no. 600100-600102, 600129



Safety barrier

Order no. 70746-70748



Front-side railing

Order no. 650103-650105

More information from page 252 onwards

10	11	12	13	14	15	16	17	18
3,180	3,390	3,600	3,800	4,010	4,220	4,430	4,640	4,850
2,080	2,290	2,500	2,700	2,910	3,120	3,330	3,540	3,750
2,801	3,013	3,221	3,430	3,639	3,851	4,061	4,273	4,523

600430	600431	600432	600433	600434	600435	600436	600437	600438
--------	--------	--------	--------	--------	--------	--------	--------	--------

600450	600451	600452	600453	600454	600455	600456	600457	600458
--------	--------	--------	--------	--------	--------	--------	--------	--------

600470	600471	600472	600473	600474	600475	600476	600477	600478
--------	--------	--------	--------	--------	--------	--------	--------	--------

600510	600511	600512	600513	600514	600515	600516	600517	600518
--------	--------	--------	--------	--------	--------	--------	--------	--------