

Accessories and spare parts

Stairs, bridging steps, walkways

Proven accessory components make our products even more practical and safe to use. What is more, we also continue to offer the most popular accessory and spare parts after many years, most of which are supplied for self-assembly.

04



Undercarriages for platform stairs

- For the convenient lifting and lowering of the platform stairs before and after the process
- With hand or foot operating lever for ergonomic actuation
- Available in the most diverse designs

Configure online now:
www.steigtechnik.de/konfigurator

ZBS 1-2



- 2 swivel castors can be raised and lowered by operating lever
- Operating lever with safety bolt either on right or left
- Working stroke 50 mm
- Swivel castors can be selected from Ø 125 mm to Ø 200 mm

ZBS 1-4



- 4 swivel castors can be raised and lowered by operating lever
- Operating lever with safety bolt either on right or left
- Working stroke 50 mm
- Swivel castors can be selected from Ø 125 mm to Ø 200 mm

ZBS 2-2



- 2 swivel castors can be operated with the foot lever
- Swivel castors can be selected from Ø 100 mm to Ø 200 mm
- The position of the foot operating lever can vary depending on the step surface

ZBS 2-4



- 4 swivel castors can be operated with the foot lever
- Swivel castors can be selected from Ø 100 mm to Ø 200 mm
- The position of the foot operating lever can vary depending on the step surface

ZBS 3-2



- 2 swivel castors can be operated with hydraulic brake
- Swivel castors Ø 160 mm or Ø 200 mm can be selected

ZBS 3-4



- 4 swivel castors can be operated with hydraulic brake
- Swivel castors Ø 160 mm or Ø 200 mm can be selected

ZBS 4



- 2 swivel castors can be operated with the foot lever
- Foot operating lever on right next to first step
- Swivel castors, Ø 100 mm

ZBS 5



- 2 swivel castors can be operated with the foot lever located in-between
- Swivel castors, Ø 125 mm



Fig.: Order no. 600100

Wall bracket

Suitable for step width	600 mm	800 mm	1,000 mm
Order no.	600100	600101	600102
With handrail on both sides			
Order no.	600101	600102	600129



Fig.: Order no. 650103

Front-side railing

Suitable for step width	600 mm	800 mm	1,000 mm
Order no.	650103	650104	650105



Fig.: Order no. 690070

Support frame for stairs

- 45° / 60° / 90° below the platform

Platform height in mm	500-1,000	1,001-2,000	2,001-3,000	3,001-4,000
Order no.	690070	690075	690080	690085

Storage tray for railing ≥ 800 mm



Order no. 300108

- L x W x H mm 100 x 300 x 600

Foot bracket for floor-mounted installation



Order no. 600125

- 1 set = 2 pcs.

Safety rope



Order no. 70739

- Safety rope with snap hook and eye bolt for platform widths 600/800/1,000 mm

Platform width	600 mm	800 mm	1,000 mm
Order no.	70738	70739	70740

Safety rope



- Safety rope with snap hook and eye bolt for platform width 600 mm.
- Suitable for bringing 70° with order no. 303404-303408

Platform width	600 mm
Order no.	50125



Order no. 19274 and order no. 19276

Storage tray

- Incl. holder and attachment
- Suitable for clamping range Ø 38–51 mm universally usable
- Payload: approx. 10 kg

Dimensions	500 x 200 mm	800 x 300 mm
Order no.	19274	19276

Storage tray



- Incl. holder and attachment
- Suitable for bringing 70° with order no. 303404–303408
- Payload: approx. 10 kg
- 500 x 220 mm

Order no.	19273
-----------	-------

Hook



- Hook holder for push-fit railing, Ø 40 mm

Order no.	70750
-----------	-------

Safety barrier



Order no. 70747

- Safety barrier with knee board for platform widths 600/800/1,000 mm

Platform width	600 mm	800 mm	1,000 mm
Order no.	70746	70747	70748

Snow pusher with holder



- Sturdy and robust aluminium snow pusher
- Insulated and non-slip handle bar
- For all de-icing systems and scaffolds
- Holder included

Length in mm	3,200
Width in mm	835
Weight in kg	3.0
Order no.	70531

Telescopic safety door

- In accordance with DIN EN ISO 14122
- Safety door for platform widths 600/800/1,000 mm, fixed, adjustable
- On-site adaptation to intermediate sizes possible through additional bore holes
- Simple installation

Order no.	70772
-----------	-------

Safety doors

- In accordance with DIN EN ISO 14122
- Safety door for platform widths 600/800/1,000 mm
- Minimum length of the platform: 600 mm width = length 1,000 mm / 800 mm width = length 1,200 mm / 1,000 mm width = length 1,400 mm
- Simple installation

	600 mm	800 mm	1,000 mm
Order no.	70735	70736	70737



Step padding retrofit kit clip-step

- Suitable for bringing 70° with order no. 303404–303408
- Optimised non-slip protection, safe footing, comfortable stance. Is clipped on to cover the entire surface precisely

Order no. bridge	Order no. retrofit kit
303404	50262
303405	50264
303406	50266
303407	50268
303408	50270

Retrofit kit for clip-step R 13 step padding

- Suitable for bringing 70° with order no. 303404–303408
- Certified non-slip surface
- Improved work safety specially in wet and oily work environments
- Is clipped on to cover the entire surface precisely

Order no. bridge	Order no. retrofit kit
303404	41652
303405	41654
303406	41656
303407	41658
303408	41660

Inspection sticker

- The inspection sticker is standard on most products upon delivery
- Within the scope of the recurring inspections, this can be stuck over with a new inspection date
- 1 PU = 50 pcs.

Size	40 x 40 mm
Order no.	19175

Inventory sticker

- For quick and easy identification of ladders, scaffolds, etc.
- Pre-printed fields for department and inventory number
- Integrated inspection sticker, which can be overwritten or provided with a new inspection date as part of the mandatory recurring inspections
- 1 PU = 50 pcs.

Size	40 x 150 mm
Order no.	19176