




Fig.: Order no. 33214 and order no. 19900

Double-sided rung ladder wood





- Double-sided rung ladder made of wood
- Including tool tray
- Pine/fir or knot-free Caroline pine side-rails, beech
- Smooth side-rail surface, thanks to mortised rungto-side-rail connection
- Connecting bolts between the side-rails act as a ladder holder and rung tensioner
- Sturdy steel hinges
- Supplied as standard with practical bucket hook
- Spreader lock with two galvanized steel chains
- Rung spacing: 280 mm
- Maximum load: 150 kg
- These products are covered by the statutory

Approx. max. working height in m	2.5	2.8	3.0	3.3	3.6	4.2
Number of rungs	2 x 4	2 x 5	2 x 6	2 x 7	2 x 8	2 x 10
Ladder length in m	1.23	1.51	1.79	2.07	2.34	2.91
Base spread in m	0.83	0.99	1.09	1.25	1.30	1.50
Lower outer width in m	0.50	0.53	0.56	0.59	0.62	0.68
Upper outer width in m	0.38	0.38	0.38	0.38	0.38	0.38
Depth of side-rails in mm	60	60	60	60	60	60
Weight in kg	6.5	7.5	10.0	10.5	14.5	17.5
Order no.	33208	33210	33212	33214	33216	33220

Suitable accessories



R 13 hook-in platform Order no. 19900



Outside shoe for wooden ladder Order no. 19619



XL wall-mounted ladder holder Order no. 19841

Find out more from page 110 onwards

Double-sided rung ladder GFRP





Tested to 28.000



compliant accessories are required

- Double-sided rung ladder made of glass-fibre reinforced plastic
- Including tool tray
- Side-rails and rungs made of glass-fibre reinforced plastic profiles (min. 10 years ageing resistance)
- Grooved square rungs, 28 x 29 mm
- Without fillers
- High-strength rung-to-side-rail connection
- nivello® ladder shoes
- Solid, galvanised steel hinges with screw attachment
- Plastic end caps on upper side-rail end
- Spreader lock with two high-strength nylon straps
- Rung spacing: 280 mm
- Maximum load: 150 kg
- Suitable for working near or on live parts
- Tested up to 28,000 V as per DIN EN 61475:2002 Category 1



Note: Products with glass-fibre reinforced plastic content are non-returnable due to their sensitivity

Approx. max. working height in m	2.5	2.75	3.0	3.5	4.0	4.5	5.0
Number of rungs	2 x 4	2 x 5	2 x 6	2×8	2 x 10	2 x 12	2 x 14
Ladder length in m	1.27	1.55	1.83	2.39	2.95	3.51	4.07
Base spread in m	0.94	1.11	1.28	1.55	1.98	2.31	2.67
Lower outer width in m	0.48	0.50	0.53	0.59	0.65	0.71	0.77
Depth of side-rails in mm	73	73	73	73	73	73	73
Weight in kg	10.0	10.5	12.0	15.5	20.0	24.5	28.0
Order no.	36404	36405	36406	36408	36410	36412	36414



Suitable accessories







XL wall-mounted ladder holder Order no. 19841

Find out more from page 110 onwards

43 42