



Fig.: Order no. 40612

Product description

- Aluminium step straight ladder
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm
- 4-fold edged step-to-side-rail connection
- ergo-pad® grip area
- Step spacing: 235 mm
- Ladder width: 420 mm (without stabiliser)
- Ladder inclination: 70°
- Available with and without stabiliser
- Can optionally be equipped with clip-step step padding
- Maximum load: 150 kg

Step straight ladder with standard stabiliser



Steps 80 mm



Standard stabiliser
with non-slip ladder shoes
(supplied loose from ladder length 3.0 m onwards)



Fig.: Order no. 40612

Approx. max. working height in m	Without stabiliser Not required by standards.						
	2.8	3.1	3.6	4.1	4.6	5.1	5.6
Number of steps	6	8	10	12	14	16	18
Ladder length in m	1.65	2.15	2.65	3.14	3.64	4.14	4.64
Stabiliser width in m	-	-	-	0.93	0.93	0.93	0.93
Depth of side-rails in mm	73	73	73	73	73	73	73
Base area in m	0.58	0.75	0.92	1.09	1.26	1.43	1.60
Weight in kg	4.5	5.5	7.0	9.0	10.5	11.64	13.0
Order no.	40306	40308	40310	40612	40614	40616	40618

Safety. Made in Germany.



Standard stabiliser



nivello® ladder shoes



ergo-pad® grip area



4-fold edged step-to-side-rail connection

Details on the relevant product page at www.steigtechnik.de

Suitable accessories




Retrofit stabiliser
Order no. 30361

Find out more from page 110 onwards

Accessory packages

Our kits make everyday working life safer, more efficient and more comfortable.
See page 108 onwards for more



Secure footing outdoors



Practical aids 2



Ladder head protection, complete set

Step straight ladder without stabiliser



Steps 80 mm



nivello® ladder shoes
with patented 2-axis inclination technology



Only for intended use
(e.g. ladder head protection)



Fig.: Order no. 40312

Approx. max. working height in m	2.8	3.1	3.6	4.1	4.6	5.1	5.6
Number of steps	6	8	10	12	14	16	18
Ladder length in m	1.65	2.15	2.65	3.15	3.65	4.15	4.65
Depth of side-rails in mm	73	73	73	73	73	73	73
Base area in m	0.58	0.75	0.92	1.09	1.26	1.43	1.60
Weight in kg	4.5	5.5	7.0	8.0	9.0	11.0	12.5
Order no.	40306	40308	40310	40312	40314	40316	40318