



Fig.: Order no. 33710

## **Product description**

- Step straight ladder made of wood
- Side-rails and steps made of finger-jointed pine or knot-free Carolina pine
- Grooved steps with a depth of 92 mm
- Steps inserted into side-rail with a threaded rod
- Oblique side-rail end for optimum wall contact or attachment
- Step spacing: 235 mm
- Ladder width: 420 mm (without stabiliser)
- Ladder inclination: 70°
- Available with and without stabiliser
- Maximum load: 150 kg







Retrofit stabiliser Order no. 30370

Find out more from page 110 onwards

## Accessory packages

Our kits make everyday working life safer, more efficient and more comfortable.

See page 108 onwards for more



Ladder head protection, complete set

## Step straight ladder, wood, with standard stabiliser



Steps 92 mm



Wooden stabiliser with non-slip ladder shoes (supplied loose from ladder length 3.0 m onwards)



Fig.: Order no. 33722

		Not required by standards			
Approx. max. working height	in m 2.7	3.17	3.64	4.06	
Number of steps	6	8	10	12	
Ladder length in m	1.69	2.19	2.69	3.16	
Stabiliser length in m	-	-	-	0.93	
Depth of side-rails in mm	70	70	70	70	
Weight in kg	5.5	7.5	9.0	13.4	
Order no	33706	33708	33710	33722	

Milhard and shills

## Step straight ladder, wood without stabiliser



Steps 92 mm



Only for intended use (e.g. ladder head protection)



Fig.: Order no. 33712

Approx. max. working height in m	2.7	3.17	3.64	4.06
Number of steps	6	8	10	12
Ladder length in m	1.69	2.19	2.69	3.13
Depth of side-rails in mm	70	70	70	70
Weight in kg	5.5	7.5	9.0	11.5
Order no.	33706	33708	33710	33712

48 49