




Fig.: Order no. 33116

Product description



- Rung straight ladder made of wood
- Side-rails made of finger-jointed pine or knot-free Carolina pine, ash rungs
- Smooth side-rail surface, thanks to mortised rung-to-side-rail connection
- Rung spacing: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Available with and without stabiliser
- Maximum load: 150 kg

Rung straight ladder, wood with stabiliser



Rungs




Wooden stabiliser
with non-slip ladder shoes
(supplied loose from ladder length 3.0 m onwards)




Fig.: Order no. 33115

Approx. max. working height in m	Without stabiliser Not required by standards.				
	3.0	3.5	4.1	4.7	5.3
Number of rungs	6	8	10	12	14
Ladder length in m	1.92	2.48	3.00	3.60	4.16
Stabiliser width in m	-	-	-	0.93	0.93
Depth of side-rails in mm	61	61	61	70	70
Weight in kg	4.0	6.0	7.5	12.9	13.4
Order no.	33106	33108	33110	33115	33116


Safety. Made in Germany.



Standard stabiliser



Rungs



Finger-jointed pine

Details on the relevant product page at www.steigtechnik.de

Suitable accessories



Retrofit stabiliser
Order no. 30370



R 13 hook-in platform
Order no. 19900

Find out more from page 110 onwards

Accessory packages

In addition to sets that ensure a safe footing, there are also packages with practical aids or to comply with the TRBS regulations.

See page 108 onwards for more



Secure footing



Practical aids 1



Ladder head protection, complete set

Rung straight ladder, wood without stabiliser



Rungs



Only for intended use
(e.g. ladder head protection)



Fig.: Order no. 33112

Approx. max. working height in m	3.0	3.5	4.1	4.7	5.3
Number of rungs	6	8	10	12	14
Ladder length in m	1.92	2.48	3.00	3.60	4.16
Depth of side-rails in mm	61	61	61	70	70
Weight in kg	4.0	6.0	7.5	11.0	11.5
Order no.	33106	33108	33110	33112	33114