



Fig.: Order no. 35012 with order no. 19910

Product description



Tested
to 1,000
volts



Appropriate accessories are
required for TRBS-compliant
work

- Rung straight ladder made of GFRP / aluminium
- Side-rails made of glass-fibre reinforced plastic profiles (min. 10 years ageing resistance)
- Grooved square rungs 30 x 30 mm, aluminium
- 4-fold edged rung-to-side-rail connection
- Rung spacing: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Available with and without stabiliser
- Maximum load: 150 kg
- Suitable for working near or on live parts
- Tested up to 1,000 volts as per DIN EN 61478:2002 Clause 6.5.1 and A1:2004 Category 1

Note: Products with glass-fibre reinforced plastic content are non-returnable due to their sensitivity

Rung straight ladder made of glass-fibre reinforced plastic / aluminium with stabiliser



Rungs



GFRP stabiliser
with non-slip ladder shoes
(supplied loose from ladder length
3.0 m onwards)



Fig.: Order no. 35312

	Without stabiliser Not required by standards.				
Approx. max. working height in m	3.0	3.6	4.1	4.7	5.3
Number of rungs	6	8	10	12	14
Ladder length in m	1.91	2.47	3.00	3.58	4.14
Stabiliser width in m	-	-	-	0.93	0.93
Depth of side-rails in mm	58	58	58	58	58
Weight in kg	4.5	5.5	7.0	9.5	10.6
Order no.	35006	35008	35010	35312	35314

Safety. Made in Germany.

GFRP stabiliser

nivello®
ladder shoes

4-fold edged
rung-to-side-rail
connection

Details on the relevant product page at www.steigtechnik.de

Suitable accessories



Retrofit stabiliser
Order no. 30373



R 13 hook-in step
Order no. 19910

Find out more from page 110 onwards

Accessory packages

In addition to sets that ensure a safe footing, there are also packages with practical aids or to comply with the TRBS regulations.

See page 108 onwards for more



**Secure footing
outdoors**



Practical aids 2



**Ladder head protection,
complete set**

Rung straight ladder made of glass-fibre reinforced plastic / aluminium without stabiliser



Rungs



nivello® ladder shoes
with patented 2-axis inclination
technology



Only for intended use
(e.g. ladder head protection)



Fig.: Order no. 35012

Approx. max. working height in m	3.0	3.6	4.1	4.7	5.3
Number of rungs	6	8	10	12	14
Ladder length in m	1.91	2.47	3.00	3.58	4.14
Depth of side-rails in mm	58	58	58	58	58
Weight in kg	4.5	5.5	7.0	8.5	9.5
Order no.	35006	35008	35010	35012	35014