



Fig.: Order no. 36812 with order no. 19910

Product description

- 

Tested to 28,000 volts
- 

Accessories may be required to comply with TRBS (insulation voltage = 1,000 V)
- Rung straight ladder made of glass-fibre reinforced plastic
 - Side-rails and rungs made of glass-fibre reinforced plastic profiles (min. 10 years ageing resistance)
 - Grooved square rungs, 28 x 29 mm
 - Without fillers
 - High-strength rung-to-side-rail connection
 - Rung spacing: 280 mm
 - Ladder width: 420 mm (without stabiliser)
 - Available with and without stabiliser
 - Maximum load: 150 kg
 - Suitable for working near or on live parts
 - Tested up to 28,000 volts as per DIN EN 61478:2002 Category 1

Note: Products with glass-fibre reinforced plastic content are non-returnable due to their sensitivity

Rung straight ladder made of glass-fibre reinforced plastic with stabiliser

- 

Rungs
- 

GFRP stabiliser
with non-slip ladder shoes
(supplied loose from ladder length 3.0 m onwards)



Fig.: Order no. 36814

Approx. max. working height in m	Without stabiliser Not required by standards.				
	3.0	3.6	4.1	4.7	5.3
Number of rungs	6	8	10	12	14
Ladder length in m	1.92	2.48	3.00	3.59	4.15
Stabiliser width in m	-	-	-	0.93	0.93
Depth of side-rails in mm	73	73	73	73	73
Weight in kg	6.0	7.5	9.0	11.9	13.8
Order no.	36006	36008	36010	36812	36814

Safety. Made in Germany.



GFRP stabiliser



nivello® ladder shoes



High-strength rung-to-side-rail connection

Details on the relevant product page at www.steigtechnik.de

Suitable accessories

- 

Retrofit stabiliser
Order no. 30373
- 


R 13 hook-in step
Order no. 19910


Find out more from page 110 onwards


Accessory packages

In addition to sets that ensure a safe footing, there are also packages with practical aids or to comply with the TRBS regulations.

See page 108 onwards for more


- 


Secure footing
- 


Practical aids 1
- 

Ladder head protection, complete set

Rung straight ladder made of glass-fibre reinforced plastic without stabiliser

- 

Rungs
- 

nivello® ladder shoes
with patented 2-axis inclination technology
- 

Only for intended use
(e.g. ladder head protection)



Fig.: Order no. 36014

Approx. max. working height in m	3.0	3.6	4.1	4.7	5.3
Number of rungs	6	8	10	12	14
Ladder length in m	1.92	2.48	3.00	3.59	4.15
Depth of side-rails in mm	73	73	73	73	73
Weight in kg	6.0	7.5	9.0	10.5	12.0
Order no.	36006	36008	36010	36012	36014