

NANUKTM
PROFESSIONAL PROTECTIVE CASES








MEDIUM
SERIES **920**

SPECIFICATIONS

Interior dimensions	L15.0" × W10.5" × H6.2" L381mm x W267mm x H157mm
Exterior dimensions	L16.7" × W13.4" × H6.8" L424mm × W340mm × H173mm
Weight (empty)	5.1 lbs 2.3 kg
Lid depth	2.1" 53mm
Base depth	4.1" 104mm
Max buoyancy	40 lbs 18.1 kg
Temperature range	Min -20°F (-29°C) Max 140°F (60°C)
Airline cabin carry-on	Yes
Watertight	Yes - IP67
Warranty	Conditional lifetime guarantee



CERTIFICATIONS

	IPX7 INGRESS PROTECTION - WATERPROOF
	IP6X INGRESS PROTECTION - DUSTPROOF
	ATA SPECIFICATION 300 - CATEGORY 1 IMPACT
	ASTM D-4169 DC-18 - DROP TEST 48cm (19") min.
	ASTM D-4169 DC-18 - VIBRATION
	ASTM D-4169 DC-18 - RAINFALL
	MIL-STD-810F - IMMERSION 1 meter (3.28 ft)

MATERIALS

Case shell	NK-7 high impact polypropylene
Latches	Nylon 66
Handle	NK-7 high impact polypropylene TPE
Purge valve	Nylon 66 Gore® membrane Silicone washers
Pins/hardware	304 stainless steel
Gasket	EPDM

STANDARD FEATURES

- 1 - Powerclaw latching system
- 2 - Waterproof IP67 rated
- 3 - Impact resistant NK-7 resin
- 4 - Padlockable
- 5 - Stackable
- 6 - Molded-in bezel system
- 7 - Soft grip handle stay
- 8 - Automatic pressure release valve
- 9 - Integrated lid stay
- 10 - 100% stainless steel hardware
- 11 - Lifetime guarantee



AVAILABLE COLORS



AVAILABLE OPTIONS



CUSTOM OPTIONS

