



Fig. Order No. 115301

## Standard aluminium folding scaffolding for narrow passages

Whenever space is extremely limited, folding scaffoldings are the right solution: They fit through every German standard door and require only little space when folded together.

When unfolded, the following scaffolding dimensions are available: 0.75 x 1.80 m or 1.35 x 1.80 m, with which working heights of up to 3.00 m can be reached.

4 swivel castors of 125 mm dia. with arrester. Self-locking folding hinge. The non-slip platform ensures safe standing conditions.

Delivery is made in component groups. Once assembled completely, the scaffolding can be quickly assembled and disassembled without tools.

GS tested, load capacity 1.5 kN/m<sup>2</sup>



Fig. Order No. 27945

## Technical overview:

- GS tested
- Foldable
- Self-locking folding hinge
- Working height approx. 3.00 m
- Scaffolding dimensions: 0.75 x 1.80 m / 1.35 x 1.80 m
- 4 Swivel castors 125 mm dia. with arrester
- Load capacity: 1.5 kN/m<sup>2</sup>.



Fig. Order No. 115401

Parts list	Order No.	115301	115401
Folding frame unit with 4 swivel castors Ø 125 mm with arresting brake	27945	1	-
Folding frame unit with 4 swivel castors Ø 125 mm with arresting brake	27946	-	1
Platform without trapdoor	27254	1	2

Working height approx. m	3.00	3.00
Scaffolding height m	1.72	1.72
Platform height m	0.99	0.99
Scaffolding dimensions m	0.75 x 1.80	1.35 x 1.80
Weight approx. kg	36.0	54.0
Order No.	115301	115401