



Fig. Order No. 39002

Steel and wood step stool

Steps with a depth of 150 mm, varnished, cover plate with hand hole, side-rails made of steel, grey coating (RAL 7023), non-slip ladder shoes.

| Working reach up to approx. m | 2,40 | 2,60 | 2,80 |
|-----------------------------------|-------------|-------------|-------------|
| Height of cover plate m | 0,49 | 0,73 | 0,97 |
| Base surface WxD m | 0,46 x 0,62 | 0,50 x 0,82 | 0,54 x 1,00 |
| Number of steps incl. cover plate | 2 | 3 | 4 |
| Weight approx. kg | 7,0 | 10,5 | 13,6 |
| Order No. | 39002 | 39003 | 39004 |



Fig. Order No. 39012

Steel and wood step stool with braked fixed castors

As described above but complete with 1 set (= 4 pcs.) braked fixed castors for self-installation. The castors are designed to move in longitudinal direction and brake automatically when stepping on the step stool.

| Working reach up to approx. m | 2,40 | 2,60 | 2,80 |
|-----------------------------------|-------------|-------------|-------------|
| Height of cover plate m | 0,49 | 0,73 | 0,97 |
| Base surface WxD m | 0,46 x 0,62 | 0,50 x 0,82 | 0,54 x 1,00 |
| Number of steps incl. cover plate | 2 | 3 | 4 |
| Weight approx. kg | 10,2 | 13,7 | 16,8 |
| Order No. | 39012 | 39013 | 39014 |



Fig. Order No. 39022

Steel and wood step stool with braked castors

As described above but complete with 1 set (= 4 pcs.) braked castors for self-installation. In this variant, the step stool can be rotated on the spot or moved around bends. The castors brake automatically when stepping on the step stool.

| Working reach up to approx. m | 2,40 | 2,60 | 2,80 |
|-----------------------------------|-------------|-------------|-------------|
| Height of cover plate m | 0,49 | 0,73 | 0,97 |
| Base surface WxD m | 0,46 x 0,62 | 0,50 x 0,82 | 0,54 x 1,00 |
| Number of steps incl. cover plate | 2 | 3 | 4 |
| Weight approx. kg | 11,1 | 14,6 | 17,7 |
| Order No. | 39022 | 39023 | 39024 |

Shipment of the step stools in disassembled parts. Instructions are attached.