



Fig. Order No. 50088

| Working reach up to approx. m | 2,95 | 3,15 | 3,40 | 3,65 | 3,90 | 4,10 | 4,35 |
|---|-------|-------|-------|-------|-------|-------|-------|
| Total height m | 1,67 | 1,91 | 2,15 | 2,38 | 2,62 | 2,85 | 3,09 |
| Platform height m | 0,95 | 1,19 | 1,42 | 1,66 | 1,89 | 2,13 | 2,36 |
| Step length m | 1,00 | 1,15 | 1,29 | 1,43 | 1,60 | 1,75 | 1,90 |
| Bottom outside width m | 0,61 | 0,64 | 0,66 | 0,69 | 0,72 | 0,75 | 0,78 |
| Number of steps incl. standing platform | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| Weight approx. kg | 10,3 | 11,7 | 12,6 | 13,9 | 15,8 | 17,2 | 18,4 |
| Order No. | 50084 | 50085 | 50086 | 50087 | 50088 | 50089 | 50090 |

Single-sided step ladder made of aluminium

With large standing platform and tray

Grooved steps with a depth of 80 mm. Durable step-to side-rail connection, non-slip nivello® ladder shoes and ergo-pad® grip area. Large standing platform approx. 400 x 400 mm; top tray approx. 350 x 200 mm, foldable.

Optimised 'safe-cap' ladder joint with extra large lay-on surface, 3-fold riveting and increased wall thickness for even more ladder stability and service life.

2 handrails approx. 750 mm in length, for self-installation (as from order No. 50088, 1300 mm in length).

Spread securing using 2 high-tensile nylon belts.

High stability thanks to conical construction.

Spacing between steps 235 mm, ladder inclination 20°.



Fig. Order No. 51086



| Working reach up to approx. m | 2,95 | 3,15 | 3,40 | 3,65 | 3,90 | 4,10 | 4,35 |
|---|-------|-------|-------|-------|-------|-------|-------|
| Total height m | 1,67 | 1,91 | 2,15 | 2,38 | 2,62 | 2,85 | 3,09 |
| Platform height m | 0,95 | 1,19 | 1,42 | 1,66 | 1,89 | 2,13 | 2,36 |
| Step length m | 1,16 | 1,31 | 1,45 | 1,60 | 1,76 | 1,91 | 2,06 |
| Bottom outside width m | 0,61 | 0,64 | 0,66 | 0,69 | 0,72 | 0,75 | 0,78 |
| Number of steps incl. standing platform | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| Weight approx. kg | 13,2 | 14,6 | 15,5 | 16,8 | 18,7 | 20,1 | 21,3 |
| Order No. | 51084 | 51085 | 51086 | 51087 | 51088 | 51089 | 51090 |

Single-sided step ladder made of aluminium with castors and handles

With large standing platform and tray

Grooved steps with a depth of 80 mm. Durable step-to side-rail connection, non-slip nivello® ladder shoes, with 2 lifting rollers, 125 mm dia., 2 handles, galvanised steel. Large standing platform approx. 400 x 400 mm; top tray approx. 350 x 200 mm, foldable.

Optimised 'safe-cap' ladder joint with extra large lay-on surface, 3-fold riveting and increased wall thickness for even more ladder stability and service life.

2 handrails approx. 750 mm in length, for self-installation (as from order No. 51088, 1300 mm in length).

Rigid connections through metal struts removable on both sides for easy self-installation (instructions attached).

High stability thanks to conical construction.

Spacing between steps 235 mm, ladder inclination 20°.

NEW!

clip-step and clip-step R13 step padding:
See chapter Accessories for retrofit kits for these step ladders.