

Double-sided working platform made of aluminium

Stable welded round aluminium tube construction, upper stepping surface 410 x 300 mm for comfortable and safe standing.

Side-rail ends with non-slip plastic shoes.

Shipment in disassembled parts. Assembly instruction included.

Step and platform version: Grooved aluminium

Working height up to approx. m	2.50	2.70	3.00
Platform height m	0.49	0.73	0.97
Upper stepping surface W x D m	0.41 x 0.30	0.41 x 0.30	0.41 x 0.30
Base area WxD m	0.54 x 0.73	0.59 x 1.15	0.64 x 1.50
Number of steps	2 x 2	2 x 3	2 x 4
Weight approx. kg	6.9	11.0	15.5
Order no.	50059	50060	50061



Fig. Order no. 50060 with 4 pcs. spring-loaded braking castors order no. 50069

Step and platform version: Wood

Working height up to approx. m	2.50	2.70	3.00
Platform height m	0.49	0.73	0.97
Upper stepping surface W x D m	0.41 x 0.30	0.41 x 0.30	0.41 x 0.30
Base area WxD m	0.54 x 0.73	0.59 x 1.15	0.64 x 1.50
Number of steps	2 x 2	2 x 3	2 x 4
Weight approx. kg	9.5	13.3	19.5
Order no.	50065	50066	50067



Fig. Order no. 50065

Step and platform version: Steel grating

Working height up to approx. m	2.50	2.70	3.00
Platform height m	0.49	0.73	0.97
Upper stepping surface W x D m	0.41 x 0.30	0.41 x 0.30	0.41 x 0.30
Base area WxD m	0.54 x 0.73	0.59 x 1.15	0.64 x 1.50
Number of steps	2 x 2	2 x 3	2 x 4
Weight approx. kg	11.1	16.3	23.0
Order no.	50062	50063	50064



Fig. Order no. 50064

Accessories:

	Order no.
1 set = 4 pcs. spring-loaded braking castors Ø 50 mm for self-installation	50068 suitable for platforms with 2 steps
1 set = 4 pcs. spring-loaded braking castors Ø 50 mm for self-installation	50069 suitable for platforms with 3-4 steps



Fig. Order no. 50068/50069