

# 1510

## Protector

Carry-On Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Maximum airline carry on size\*
- · Strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open Double Throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension handle
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee\*\*
- \* Check with your airline for exact measurement requirements.
- \* Where applicable by law



## **CONFIGURATIONS**



1510 Standard



**1514** With Padded Dividers



1510NF No Foam



**1510TP** With TrekPak Divider System



1510WF



**1510TPF** TrekPak / Foam Hybrid

#### **DIMENSIONS**

Interior (L×W×D) 19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm) Exterior (L×W×D) 22.00 x 13.81" x 9.00 (55.9 x 35.1 x 22.9 cm)

 Lid Depth
 1.79" (4.5 cm)

 Bottom Depth
 5.79" (14.7 cm)

 Total Depth
 7.58" (19.3 cm)

 Int Volume
 0.96 ft³ (0.027 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

#### **MATERIALS**

**Body** Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

### **COLOURS**

Black Desert Tan Yellow

## WEIGHT

 Weight With Foam
 13.60 lbs (6.2 kg)

 Weight Empty
 11.99 lbs (5.4 kg)

 Buoyancy
 64.15 lbs (29.1 kg)

 Master Pack Weight
 32.43 lbs (14.7 kg)

#### **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

# **CERTIFICATIONS**

IP67

Def Stan 81-41 STANAG 4280

# FOAM PROPERTIES

Layer 1 (Lid) 1.81" Convolute
Layer 2 (Base) 0.50" Pad

Layer 3 (Base)2.63" Pick N PluckLayer 4 (Base)2.63" Pick N Pluck

#### **OTHER**

Wheels 2
Extendable Handle yes
Master Pack 2
Nameplate yes
Reduced Area yes
Military yes

### **ACCESSORIES**



**1511** 4 pc. Replacement Foam Set



**1513** Replacement O-ring



**1515** Padded Divider Set



**1519** Lid Organizer



**1510EUTP** TrekPak Case Divider Kit







**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel

#### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 01-29-20