



1525

Air

Peli™ Air cases are the first in a series of remarkable innovations engineered by Peli, the pioneers of protective cases. For over 40 years Peli has designed and crafted the most influential protective cases in the world, and we're just getting started.

With the launch of the Peli™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic Purge Valve - Keeps water and dust out while balancing air pressure
- Super-light proprietary HPX2™ Polymer
- Business card holder



CONFIGURATIONS



1525
Standard



1525NF
No Foam



1525WD
With Padded Dividers



1525TP
With TrekPak Divider System



1525WF
With Foam

DIMENSIONS

Interior (L×W×D)	20.50 x 11.31" x 6.75 (52.1 x 28.7 x 17.1 cm)
Exterior (L×W×D)	21.96 x 13.97" x 7.49 (55.8 x 35.5 x 19 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	4.75" (12.1 cm)
Total Depth	6.75" (17.1 cm)
Int Volume	0.91 ft ³ (0.026 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

Black	Orange	Silver	Yellow
-------	--------	--------	--------

WEIGHT

Weight With Foam	7.13 lbs (3.2 kg)
Weight Empty	5.99 lbs (2.7 kg)

Buoyancy 57.90 lbs (26.3 kg)

TEMPERATURE

Minimum Temperature -60°F (-51.1 °C)

Maximum Temperature 160°F (71.1 °C)


FOAM PROPERTIES

Layer 1 (Lid) 2.03" Convolute

Layer 2 (Base) 3.75" Pick N Pluck

Layer 3 (Base) 0.70" Pad

ACCESSORIES



1525TP-KIT
TrekPak Case Divider Kit



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

info@peli.com • www.peli.com

Document created on 01-29-20