



1555

Air

Peli™ Air cases are the first in a series of remarkable innovations engineered by Peli, the pioneers of protective cases. For over 40 years Peli has designed and crafted the most influential protective cases in the world, and we're just getting started. With the launch of the Peli™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic Purge Valve - Keeps water and dust out while balancing air pressure
- Super-light proprietary HPX²™ Polymer
- Business card holder



CONFIGURATIONS



1555
Standard



1555NF
No Foam



1555WD
With Padded Dividers



1555TP
With TrekPak Divider System



1555WF
With Foam

DIMENSIONS

Interior (L×W×D)	23.00 x 12.75" x 7.50 (58.4 x 32.4 x 19.1 cm)
Exterior (L×W×D)	24.76 x 15.46" x 8.24 (62.9 x 39.3 x 20.9 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	5.50" (14 cm)
Total Depth	7.5" (19.1 cm)
Int Volume	1.27 ft ³ (0.036 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

Black	Orange	Silver	Yellow
-------	--------	--------	--------

WEIGHT


Weight With Foam	9.02 lbs (4.1 kg)
Weight Empty	7.37 lbs (3.3 kg)

Buoyancy

81.20 lbs (36.8 kg)

TEMPERATURE**Minimum Temperature** -60°F (-51.1 °C)**Maximum Temperature** 160°F (71.1 °C)

FOAM PROPERTIES**Layer 1 (Lid)** 2.03" Convolute**Layer 2 (Base)** 2.25" Pick N Pluck**Layer 3 (Base)** 2.25" Pick N Pluck**Layer 4 (Base)** 0.90" Pad

ACCESSORIES

1555TP-KIT
TrekPak Case Divider Kit



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 01-29-20