



iM2100 Storm

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



CONFIGURATIONS



iM2100
Standard



iM2100-X0000
No Foam



iM2100-X0002
With Padded Dividers



iM2100-X0001
With Foam

DIMENSIONS

Interior (L×W×D)	13.00 x 9.20" x 6.00 (33 x 23.4 x 15.2 cm)
Exterior (L×W×D)	14.20 x 11.40" x 6.50 (36.1 x 29 x 16.5 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	4.00" (10.2 cm)
Total Depth	6" (15.2 cm)
Int Volume	0.42 ft³ (0.012 m³)
Padlock Hole Diameter	1/4" (2.5 cm)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

COLOURS

 Black	 OD Green	 Yellow	 Realtree Edge
---	--	--	---

WEIGHT

Weight With Foam	4.90 lbs (2.2 kg)
Weight Empty	4.20 lbs (1.9 kg)
Buoyancy	26.20 lbs (11.9 kg)
Master Pack Weight	24.60 lbs (11.2 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

CERTIFICATIONS

MIL-STD-810F
ATA 300
FED-STD-101C


FOAM PROPERTIES

Layer 1 (Lid)	2.00" Convolute
Layer 2 (Base)	0.63" Pad
Layer 3 (Base)	1.69" Pick N Pluck
Layer 4 (Base)	1.69" Pick N Pluck

OTHER

Master Pack	4
Military	yes

ACCESSORIES

				
iM2100-FOAM 4 pc. Replacement Foam Set	iM2100-DIV Padded Divider Set	iM-STRAP-S-VER2 Padded Shoulder Strap	iM-LIDSTAY Lid Stay	iM2100-MBEZ-B Base Bezel (Metric)
				
1506TSA TSA Lock	1500D Desiccant Silica Gel			

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 01-28-20