



iM2875

Storm

Travel Case

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- Six Press & Pull Latches
- Two Padlockable Hasps
- Two Double-layered, Soft-grip Handles
- Powerful Hinges
- O-ring seal
- Telescoping Handle



CONFIGURATIONS



iM2875
Standard



iM2875-X0000
No Foam



iM2875-X0002
With Padded Dividers



iM2875-X0001
With Foam

DIMENSIONS

Interior (LxWxD)	22.50 x 21.10" x 11.40 (57.2 x 53.6 x 29 cm)
Exterior (LxWxD)	24.90 x 23.70" x 13.10 (63.2 x 60.2 x 33.3 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	9.40" (23.9 cm)
Total Depth	11.4" (29 cm)
Int Volume	3.13 ft ³ (0.089 m ³)
Padlock Hole Diameter	3/8" (7.6 cm)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

COLOURS

■ Black

■ OD Green

WEIGHT

Weight With Foam	24.60 lbs (11.2 kg)
Weight Empty	20.10 lbs (9.1 kg)
Buoyancy	194.16 lbs (88.1 kg)
Master Pack Weight	32.00 lbs (14.5 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

CERTIFICATIONS

MIL-STD-810F
ATA 300
FED-STD-101C

FOAM PROPERTIES

Layer 1 (Lid)	2.00" Convolute
Layer 2 (Base)	0.63" Pad
Layer 3 (Base)	1.78" Pick N Pluck
Layer 4 (Base)	1.78" Pick N Pluck
Layer 5 (Base)	1.78" Pick N Pluck
Layer 6 (Base)	1.78" Pick N Pluck
Layer 7 (Base)	1.78" Pick N Pluck

OTHER

Extendable Handle	yes
Master Pack	1
Military	yes

ACCESSORIES



iM2875-UTILITYORG
Utility Organizer




iM2875-FOAM
7 pc. Replacement Foam Set



iM2875-DIV
Padded Divider Set



iM-LIDSTAY
Lid Stay



iM2875-MBEZ-B
Base Bezel (Metric)



IM28XX-M4-BEZEL-L
Lid Bezel (Metric)



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 01-28-20