




Jumper selectable high or low setting to allow selection of more light output or more runtime



An industrial-duty, rechargeable, portable lantern featuring C4® LED technology for high brightness, long runtime and reliability

3 LEDs and deep dish parabolic reflectors to produce a large spot pattern. Optimized electronics provide regulated intensity

2 levels of lighting:

High: 55,000 candela peak beam intensity; 540 lumens

Low: 32,000 candela peak beam intensity; 330 lumens

Runtime:

High: High: 7 hours to the 10% output level

Low: 15 hours to the 10% output level



IPX4 rated for water-resistance

Fits existing LiteBox mounting racks

Rack meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position





Standard System – International safety orange or high visibility yellow; includes shoulder strap; includes AC and DC chargers and charge rack

Vehicle Mount System – International safety orange or high visibility yellow; includes vehicle-mountable hard-wire rack and shoulder carrying strap

Power Failure System – International safety orange or beige. "Smart" power failure circuitry automatically illuminates when the power goes off; includes AC and DC charge cords and charge rack.

Limited lifetime warranty



	FL1 STANDARD	HIGH	LOW
OUTPUT		540 LUMENS	330 LUMENS
RUNTIME		7h	15h
DISTANCE		469m	358m
INTENSITY		55,000 cd	32000cd

E-SPOT LITEBOX

Standard System

45851	E-Spot LiteBox with 120V AC/12V DC - Orange
45852	E-Spot LiteBox with 230V AC/12V DC - Orange
45853	E-Spot LiteBox with 240V AC/12V DC - Orange
45854	E-Spot LiteBox with 100V AC/12V DC - Orange
45871	E-Spot LiteBox with 120V AC/12V DC - Yellow
45872	E-Spot LiteBox with 230V AC/12V DC - Yellow
45873	E-Spot LiteBox with 240V AC/12V DC - Yellow
45874	E-Spot LiteBox with 100V AC/12V DC - Yellow

Vehicle Mount System

45855	E-Spot LiteBox Vehicle Mount - Orange
45875	E-Spot LiteBox Vehicle Mount - Yellow

Power Failure System

45857	E-Spot LiteBox Power Failure with 120V AC/12V DC - Orange
45858	E-Spot LiteBox Power Failure with 230V AC/12V DC - Orange
45859	E-Spot LiteBox Power Failure with 240V AC/12V DC - Orange
45860	E-Spot LiteBox Power Failure with 100V AC/12V DC - Orange
45867	E-Spot LiteBox Power Failure with 120V AC/12V DC - Beige
45868	E-Spot LiteBox Power Failure with 230V AC/12V DC - Beige
45869	E-Spot LiteBox Power Failure with 240V AC/12V DC - Beige
45870	E-Spot LiteBox Power Failure with 100V AC/12V DC - Beige

Without Charger

45856	E-Spot LiteBox (WITHOUT CHARGER) Orange
45866	E-Spot LiteBox (WITHOUT CHARGER) Beige
45876	E-Spot LiteBox (WITHOUT CHARGER) Yellow